



1800+2600MHz 5G Signal Repeater



OVERVIEW

ATNJ RF repeater with industrial design, combines multi mobile network signals together and improves the mobile voice and data communication, aiming to provide a more cost-effective solution for signal. ATNJ RF repeater is easy to install and maintain, which could help signal providers get fast solution.

A repeater is working as a relay between the BTS and mobiles. It picks up the strongest signal from BTS via the Donor Antenna, linearly amplifies the signal and then re-transmits it via the Indoor Signal Distribution System to the weak/blind coverage area. And the mobile signal is also amplified and re-transmitted to the BTS via the opposite direction.

FEATURES

- Improve any two mobile networks at the same time
- LCD display the input/output signal strength
- Auto isolation detect function
- Auto gain control
- Auto level control
- Auto uplink noise reduction, avoid disturbing to BTS
- Smart LCD to guide the installation
- Golden color metal industrial design

WHERE TO USE

- Indoor: Hotels, Exhibition Centers, Basement, Parking Lots, Shopping Malls, Apartments..
- Outdoor: Airport, Tunnel, Village, Mining Area, Court, Tourism Area..

APPLICATION SCENE



Technical Specification

SPECIFICATIONS		PARAMETERS	
Frequency Range		1800MHz	1710-1785/1805-1880MHz
		2600MHz	2469-2690MHz/2496-2690MHz
Band Width		1800MHz	75MHz
		2600MHz	194MHz
Gain		68 ± 3dB	
Automatic Gain Control		31dB	
MGC (Step Attenuation)		20dB@ 1dB/Step	
Output Power		17 ± 3dBm	
Spurious Emission	9 kHz -150 kHz/1kHz	≤-36dBm	
	150 kHz - 30 MHz/10kHz	≤-36dBm	
	30 MHz - 1 GHz/100kHz	≤-36dBm	
	1 GHz- 12.75 GHz/1MHz	≤-30dBm	
ACPR		Uplink Fully comply with 3GPP 36.106	
		Downlink Fully comply with 3GPP 36.106	
Unwanted emissions		Fully comply with 3GPP 36.106	
VSWR		≤2	
Ripple	GSM 900MHz	≤6dB	
	DCS 1800MHz	≤6dB	
	UMTS 2100MHz	≤6dB	
Noise Figure		≤5dB	
Delay		≤1 μ s	
I/O Impedance		50Q	
RF Connector(Customers to		SMA-Type (Female)	

Choose)	
Operating Temperature	-25°~+55°
Power Supply	DC 5V
Power consumption	≤75W
Environment Conditions	IP43
Humidity	≤90%
Weight	0.5kg
Size	205*165*45mm